L Number	Hits	Search Text	DB	Time stamp
1	8	flag$4 near coefficient near3 significan$4	USPAT; DERWENT	2002/12/23 13:13
4	8	(flag$4 near coefficient near3 significan$4) and transmi$5	USPAT; DERWENT	2002/12/23 13:13
7	4	(flag$4 near coefficient near3 significan$4) and (transmi$5 with bit)	USPAT; DERWENT	2002/12/23 13:13

	U	1	Document ID	Issue Date	Pages	Title	Current OR
1	☐	☐	US 5563960 A	19961008	22	Apparatus and method for emphasizing a selected region in the compressed representation of an image	382/239
2	☐	☐	US 5412741 A	19950502	23	Apparatus and method for compressing information	382/232
3	☐	☐	US 4096566 A	19780620	29	Modular signal processor having a hierarchical structure	710/110
4	☐	☐	EP 962099 B	19980827	1	Method of image compression by first dividing image into several image blocks - selects and flags coefficients which first become significant in group of one or more consecutive bit planes, transmits information about their positions, repeats this with each new group across entire image to be compressed	

	Current XRef	Retrieval Classif	Inventor	S	C	P	2	3	4	5
1	375/240.11; 375/240.19; 382/240; 382/248; 382/263; 382/274		Shapiro, Jerome M.	☒	☐	☐	☐	☐	☐	☐
2	358/1.9; 375/240.11		Shapiro, Jerome M.	☒	☐	☐	☐	☐	☐	☐
3			Borie, Jean-Claude et al.	☒	☐	☐	☐	☐	☐	☐
4			MONRO, D M	☒	☐	☐	☐	☐	☐	☐

	Image Doc. Displayed	PT
1	US 5563960	☐
2	US 5412741	☐
3	US 4096566	☐
4	EP 962099 A0	☐